



GYM PRO

Tacking Cleaner

FEATURES

- Dissolves rubber burns, black marks, mop treatments and soil when used for regular cleaning
- For productive, thorough cleaning of wood floors without an auto-scrubber
- Use for tacking to remove dust before sealing and/or finishing
- Will not harm wood surfaces
- Removes common food soils found on gym floors such as dried soda and candy
- Slip-Resistant – Meets ASTM D2047

PROPERTIES

Type	Polar Solvent Blend
Form.....	Clear Liquid
Odor	Characteristic Alcohol
Color	Light Blue
Weight per Gallon	8.24 Lbs.
pH	7.6
Flash Point (c.c)	103°F
Actives	> 15%
Typical Dilution	1:4

Gym Pro Tacking Cleaner is a dual-use product that cleans wood floors without leaving a residue. Use it as a tacking compound to aid in the removal of dust during sealing and refinishing. Also excellent for periodic cleaning of finished floors.



Sac-Val Janitorial Sales and Service, Inc.

Sacramento • Hayward • Santa Rosa
1-800-600-8989 • FAX (916) 923-3345
www.sacval.com

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT/MANUFACTURER'S IDENTITY

PRODUCT NAME: GYM PRO TACKING CLEANER
PRODUCT I.D. NUMBER (PIN): N.A.
PRODUCT NUMBER: NA
PRODUCT USE: Dual purpose wood floor cleaner
WHMIS CLASS: B3; D2B
DOT HAZARD CLASS: Non-Regulated
COMPANY:
SAC VAL JANITORIAL SALES INC.
2400 MANNING STREET
SACRAMENTO, CA 95815
DOT SHIPPING NAME:
N.A.
EMERGENCY PHONE: 1-800-535-5053

H.M.I.S.

	HEALTH	HAZARD RATING
1		4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant
2	FIRE	
0	REACTIVITY	
B	MAXIMUM PERSONAL PROTECTION	

A = Goggles B = Goggles & Gloves C = Goggles, Gloves & Apron

ABBREVIATION KEY: N.A. = Not Applicable N.E. = Not Established N.D. = Not Determined

SECTION 2 - HAZARDOUS INGREDIENTS INFORMATION

HAZARDOUS CHEMICAL IDENTITY	CAS NO.	%	PEL	TLV	LD50	LC50
Water	7732-18-5	60-100	N.E.	N.E.	N.D.	N.D.
1-Methoxy-2-propanol	107-98-2	7-13	100ppm	100ppm	6.6ml/kg	N.D.
Isopropanol	67-63-0	5-10	400ppm	400ppm	5.8g/kg	N.D.
Nonionic surfactants	NA	1-5	N.E.	N.E.	N.D.	N.D.

This mixture does not contain components which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR, Part 372.

SECTION 3 - PHYSICAL DATA

Color: Light Blue
Boiling Point: 100°C (212°F)
Vapor Pressure: <30 mm of Hg
pH: 7.1-8.1
Odor: Alcohol
Freezing Point: 32°C (89.6°F)
Vapor Density (Air=1): <1
1% pH: 7.0
Physical State: Liquid
Water/Oil Distribution: N.E.
Evaporation Rate (Water=1): N.E.
Specific Gravity: 0.98 gm/ml
Solubility in Water: Complete
Odor Threshold: N.E.
VOC Content: 16.0%
Weight per Gallon: 8.24 lbs./gal.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method: 103°F 38°C (C.C.)
Autoignition Temperature: N.A.
Extinguishing Media: Use water spray (fog), foam, dry chemicals, or CO₂. Use dry chemical or CO₂.
Flammable Limits: Combustible liquid.
LEL: N.E. **UEL:** N.E.
Special Fire Fighting Procedures: Use proper protective equipment.
Hazardous Combustion Products: N.A.
Unusual Fire and Explosion Hazards: Avoid sources of ignition.

SECTION 5 - REACTIVITY DATA

Chemical Stability: Stable.
Hazardous decomposition of By-Products: None known.
Incompatibility (Materials to Avoid): Strong oxidizers and sources of ignition.
Hazardous Polymerization: Will not occur.

SECTION 6 - TOXICOLOGICAL PROPERTIES

Routes of Entry: Ingestion, Inhalation, Skin contact, Eye contact.
Toxicologically Synergistic Products: None known.
Sensitization: No.
Medical Conditions Aggravated by Exposure: None known.
EFFECTS OF OVEREXPOSURE (Acute and/or Chronic):
Eyes: May cause irritation.
Skin: May cause mild irritation. May be absorbed through skin with prolonged or repeated contact.
Ingestion: May cause gastrointestinal irritation, nausea, diarrhea.
Inhalation: Exposure in poorly ventilated area may cause respiratory irritation.
Carcinogenic Effects: NO carcinogenic effect.
Mutagenic Effects: NO mutagenic effect.
Teratogenic Effects: NO teratogenic effect.
Reproductive Toxicity: NO reproductive toxicity effect.

SECTION 7 - PREVENTATIVE AND CONTROL MEASURES

Respiratory Protection: None normally required with adequate ventilation.
Ventilation: Local Exhaust: Acceptable Mechanical: Recommended
Protective Gloves: Rubber for prolonged or repeated contact.
Eye Protection: Safety glasses if splashing is likely.
Protective Clothing and Equipment: As needed to prevent wetting of skin.
Work and Hygienic Practices: Wash thoroughly after handling.
Storage Requirements: Store in cool, dry area away from sources of ignition. Empty container retains vapor and product residue; do not puncture or weld on or near container.
Other Requirements: Keep out of reach of children.
Steps to be Taken if Material is Spilled or Released: Collect and reuse if possible. Ventilate area and remove all sources of ignition. Collect on inert material (sand, clay, etc.) and place into container for proper disposal. Do not allow runoff into public waterways.
Waste Disposal: Dispose of as permitted by all federal, provincial, state and local regulatory authorities.

SECTION 8 - EMERGENCY FIRST AID PROCEDURES

FIRST AID - NOTES TO PHYSICIAN:
Eyes: Flush with a large amount of water for 15 minutes holding eyelids open.
Skin: Wash with mild soap and water.
Ingestion: Give 2-3 large glasses of water. Seek medical attention.
Inhalation: Remove to fresh air and rest. In all cases if symptoms persist, seek medical attention.
Note to Physician: No additional information.

SECTION 9 - PREPARATION INFORMATION

Prepared By: Regulatory Affairs Department
Phone: 916-923-1476