

Reorder Number - 0553-3250



# E-Z STRIP

Ultra High Active Floor Stripper

**E-Z STRIP** is a very high active formulation that quickly penetrates into multiple coats of burnished floor finish with ease. Its low odor characteristic is pleasant to use especially where odor sensitivity is a must. Fast and effective, **E-Z STRIP** will save you time and money. It effectively strips in one pass and it takes the guess work out of diluting. Simply mix 1 quart per 5 gallons of COLD water (1:20) and you're ready to go.


## DIRECTIONS FOR USE

1. Mix 1 quart per 5 gallons of **COLD WATER ONLY !!**. Anything less than 5 gallons of water will result in the stripping solution beginning to "gel". If emulsified finish begins to "gel up" on the floor, your dilution is mixed to strong. Eliminate this by adding more water which will also aid in solution pick-up.
2. Apply liberally to the floor. Depending on build-up let stand 8-12 minutes. **DO NOT LET STRIPPER DRY**. Make sure to keep floor area wet at all times. Be careful as floor can become very slippery.
3. Scrub area with floor machine/automatic scrubber with stripping brushes.
4. Pick up all the stripper/finish solution with a clean mop, wet vac. or automatic scrubber.
5. Depending upon extreme finish build-up (10+) repeat if necessary.
6. Rinse floor thoroughly with clean water. If available, add a neutralizer to your rinse water to help speed up the neutralizing rinse process. Change rinse water frequently as it becomes visibly soiled.
7. Allow floor to dry thoroughly before applying any seal / finish.

## TECHNICAL DATA

Color:	Gold
Fragrance:	Butyl
Specific Gravity:	1.00
pH Concentrate:	11.0 - 12.0
Density:	8.34 lbs/gal.
Foam:	Low
Viscosity:	Thin
Solvents:	Butyl

## HMIS RATING



Sac-Val  
JANITORIAL  
SUPPLY

Sacramento  
Hayward  
Santa Rosa  
1.800.600.8989

## MATERIAL SAFETY DATA SHEET

Date Prepared: 5-23-06 By Regulatory Department

**SECTION 1 - PRODUCT IDENTIFICATION**

Distributed By: Sac Val Janitorial Sales and Service	Emergency Phone No: 1-800-228-5635 ext. 059
Address: 2421 Del Monte Street W. Sacramento, CA	
Trade Name: E-Z STRIP	Product Type/Use: Floor Stripper
Product Code: FLS325XX	Formula: Mixture

**SECTION 2 - HAZARDOUS INGREDIENTS**

Chemical Name/Common Name:	CAS NO.	PERCENT (optional)	TLV/PEL
* 2-Butoxyethanol	111-76-2	20	25 ppm(Skin)/25 ppm (OSHA)
Benzyl Alcohol	100-51-6	30 - 50	NA
Monoethanolamine	141-43-5	20	3ppm/3ppm (OSHA)

\* Indicates toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**SECTION 3 - PHYSICAL DATA**

Boiling Point: (F) 212 (100 C) Freezing Point 32 F (0 C)	Specific Gravity: (H <sub>2</sub> O = 1.0) 1.00	pH: 11.0 - 12.0
Vapor Pressure: (mm/Hg) Not Determined	Vapor Density: Heavier than air	
Solubility In Water: Complete	Coefficient of water/oil: Not available	
Evaporation Rate (Vs ether) Slower		
Appearance and Odor: Liquid, non-viscous, GOLD color. Low Odor.	Odor Threshold: Not available	

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

Flash Point (T.C.C.): NONE
Extinguishing Media: nonflammable and non-explosive. No special procedures required.
Special Fire Fighting Procedures: none required.
Unusual Fire and Explosion Hazards: NOTHING SPECIAL.

**SECTION 5 - REACTIVE DATA**

Stability: Stable	Incompatibility: Keep away from acids and strong oxidizers.
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide and unknown organic compounds.	

**SECTION 6 - HEALTH HAZARDS**

Threshold Limit Value - Product (See Section 2 for Ingredient TLV/PEL): None Established
Primary Routes of Exposure: Eye - yes Skin - yes Oral - yes Inhalation - yes Other
Signs and Symptoms of Over-exposure (Acute): EYES: Liquid and mists will irritate the eye and may cause eye damage. INHALATION: Undiluted vapors at concentrations above the TLV will irritate the respiratory tract. Inhalation of higher concentration may cause headaches, nausea, vomiting, SKIN: Brief contact with concentrate will irritate the skin, but this irritation is reversible. Prolonged exposure may burn the skin. A single prolonged exposure may result in material being absorbed in harmful amounts. INGESTION: Liquid and vapors are corrosive to the mouth and throat. Swallowing the liquid burns and may destroy the tissues, and may cause severe abdominal pain, nausea, or vomiting.
Chronic Health Hazards: In animals, excessive overexposure to monoethanolamine has shown effects on the liver, kidneys and red blood cells.
Medical Conditions Aggravated by Over-exposure: Persons with pre-existing skin disorders, impaired respiratory function maybe more susceptible to effects.
Carcinogen or Suspect Carcinogen Ingredients: NTP - NO IARC - NO OSHA - NO

**SECTION 7 - EMERGENCY AND FIRST AID PROCEDURES**

Eyes: Flush with immediately with lots of running water for at least 15 minutes holding eyelids open. Get medical attention.
Skin: Wash skin with soap and water. Remove contaminated clothing & shoes. Wash before reuse.
Ingestion: DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep victims head below his hips to prevent his breathing vomitus into his lungs. Drink 1 to 8 glasses of water or milk to dilute. Call physician or poison control center immediately, Treat symptomatically. Do not give anything by mouth to an unconscious or convulsing person.
Inhalation: Get to fresh air.

**SECTION 8 - SPECIAL PROTECTION INFORMATION**

Respiratory Protection: Not normally required when using this product as directed.
Ventilation Requirements: Adequate ventilation required to keep exposure under TLV/PEL.
Protective Gloves: Required. the product is highly alkaline
Eye Protection: Not normally required. Goggles are recommended if splashing might occur -- wearing contact lenses is not recommended while using this product. Face shield are required if used overhead or misting or spraying.
Other: When using this product as a floor stripper or cleaner waterproof footwear must be worn. Where gross eye and skin contact may occur -- use and wear appropriate protective clothing including alkali-resistant clothing, rubber boots with pants on the outside, and rubber gloves.

**SECTION 9 - SPILL OR LEAK PROCEDURES**

Steps to be Taken if Released or Spilled: For small spills, mop or wipe up and contain. For large spills, contain by diking with absorbent material and contain. Rinse with water into sanitary sewer system where available. Keep the product out of storm drains, surface waters and soil.
Waste Disposal Methods: The contaminates of the product must be considered when disposing. Consult appropriate Federal, State and Local regulatory agencies to ascertain proper disposal procedures and comply with them.

**SECTION 10 - STORAGE AND HANDLING INFORMATION**

Precautions to be Taken in Handling and Storage: Nothing special is required. Do not mix chemicals. This product is a class 8 corrosive for storage and transport according DOT/TDG regulations. Keep container tightly closed when not in use.
---